



## OZZ SQR 5" Driving light LED

OZZ Lights SQR 5" driving light, delivering high performance in an ultra-compact form. A dynamic white/amber start-up position light adds a premium visual signature to any build. Despite its size, it outputs 5200 lumens at 5000K and reaches 1 lux at 450 m. Designed for tight installations, the SQR 5" offers flexible mounting for single, paired, or multi-lamp setups across ATVs, motorcycles, custom builds, and trucks.

<b>Art. no.</b>	88116 black/88117 white	<b>Color LED</b>	White, amber
<b>Pcs LED</b>	6	<b>Connection</b>	4-pin DT male + female
<b>Voltage</b>	10-32V DC	<b>Cable length (mm)</b>	1000
<b>Theoretical effect</b>	90 W	<b>Material bracket</b>	Stainless steel
<b>Actual effect</b>	R112: 40W, boost: 78,2W (12V DC), R112: 40W, boost: 67,2W (24V DC)	<b>Material housing</b>	Aluminum
<b>Nominal current</b>	R112: 3,33A, boost: 6,45A (12V DC), R112: 2,8A, boost: 1,66A (24V DC)	<b>Material lens</b>	Polycarbonate
<b>Functions</b>	High beam, Dynamic position light	<b>Length (mm)</b>	120
<b>Theoretical lumen</b>	7200	<b>Depth (mm)</b>	80
<b>Actual lumen</b>	R112: 2800, boost: 5200	<b>Height (mm)</b>	120
<b>1 lux @</b>	R112: 325m, boost: 450m	<b>Height including bracket (mm)</b>	139,2
<b>Kelvin</b>	5000K	<b>Operating temperature</b>	-40°C - +60°C
<b>IP-class</b>	IP68/IP69K	<b>E-mark approval</b>	ECE R149, R148
<b>Beam pattern</b>	Driving	<b>Reference number</b>	50
<b>Color housing</b>	Black/white	<b>EMC</b>	ECE R10
<b>RAL color</b>	Black RAL9011/ white RAL9003	<b>Pcs in master box</b>	12
<b>Color lens</b>	Clear	<b>EAN</b>	Black 7350166880484 White 7350166880491
		<b>Warranty</b>	3 years

