

CITROËN DISPATCH/JUMPY (2025+)

GRILLE KIT INSTRUCTIONS



WHAT'S INCLUDED

- 4x Grille Mounting Brackets
- Anti-Theft Fasteners & Key

Additionally - Kit Includes:

- 2x Triple-R 750 LED Lights
- 1x Two-Lamp Wiring Kit

TOOLS REQUIRED

- Hacksaw/Multi-tool
- Allen Key (Size 4)
- Socket Set
- Drill and Bit (Ø3.5mm)

STEP 1. Place the numbered cutting guides onto the grille as shown below.

STEP 2. Using a hacksaw or multi-tool cutter, cut the grille using the cutting guides for the vertical cuts. For the horizontal cuts, trim flush with the upper and lower horizontal grille slats. **Do not cut beyond these surfaces.**

STEP 3. Secure the mounting brackets to the lamp using the supplied M6 fasteners. Mounts with a brass insert should be tightened to a maximum of 8Nm. Mounts without a brass insert should be tightened to a maximum of 3Nm.

It is recommended to use a thread seal compound (e.g. Loctite 222).

STEP 4. Fix the lamp(s) into the grille by first engaging the outboard side, then pushing the inboard side into position. Check the full engagement of the grille mounts to the original grille.

STEP 5. Drill 3.5mm pilot holes through any pre-drilled screw mount locations on the mounts.

STEP 6. Secure with the supplied self-tapping screws into the pilot holes, taking care not to overtighten.

STEP 7. Conceal the self-tapping screws with the supplied caps.

STEP 8. Connect your lamps: for wiring information for your lamp, please refer to the printed instructions supplied with your lamp(s).

